

ExoAir™ Primer

A VOC-Compliant Adhesive Primer

Product Description

ExoAir™ Primer is a VOC-Compliant adhesive primer formulated for use with ExoAir™ 110/110LT and ExoAir™ TWF. It can be applied to common construction substrates using a brush or roller.

Basic Uses

ExoAir Primer is the primer required prior to the installation of ExoAir 110/110LT and ExoAir TWF.

Features and Benefits

ExoAir Primer is specifically formulated for use with the ExoAir line of air barrier systems, ensuring compatibility with all components required to create the full assembly. Once on the substrate, ExoAir Primer dries quickly, allowing work to proceed without delay.

Coverage Rate

Coverage rate will vary depending on porosity and texture of substrate. Approximately 250 ft²/gal (6 m²/L).

Color

Light Green

Packaging

5-gallon (19 L) pails 36 pails/pallet

Installation Information

Surfaces to be primed should be dry, clean, smooth, firm, free of dust, mud, loose mortar, wires, fins, metal projections or any other substances that might prevent placement and bonding of a continuous film. Allow primer to dry to a non-transferable tacky film, typically 15 minutes at 77°F (25°C), 50% RH.

Prime only as much substrate as will be covered with ExoAir 110/110LT or ExoAir TWF in a single day.

Storage Information

Store out of direct sunlight in a cool, well-ventilated area with temperatures ranging from 60°F to 80°F. Avoid storing directly on the floor or against an outside wall.

Availability

Immediately available from your local Tremco Sales Representative or Distributor.

Limitations

- Do not apply to damp or contaminated surfaces.

Warranty

Tremco warrants its ExoAir primers to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty expressed or implied, including warranties of merchantability and fitness for a particular purpose with respect to Tremco ExoAir primers. Tremco's sole obligation shall be, at its option, to replace or refund the purchase of the quantity of Tremco ExoAir primers proved to be defective and Tremco shall not be liable for any consequential or incidental loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

TYPICAL PHYSICAL PROPERTIES

Property

Open Time

Dry Time

Shelf Life

VOC Content (EPA Method 310)

Weight/gallon

Typical Results

6 hours

10 to 15 minutes at 77°F (25°C), 50% RH

1 year when stored in original, unopened containers at temperatures between 60°F and 80°F (15.6°C and 26.7°C)

236.1 g/L

7.68 lbs (3.48 kg)



Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213
1451 Jacobson Avenue, Ashland OH 44805 // Phone: 419.289.2050 // 800.321.6357